



Authorized Distributor
Calx Trading Corporation
1245 Amaranth Dr.
Naperville, IL 60564
Tel: 630-677-7241
Cell: 630-456-6721
www.calxtrading.com

SL-10™ Penetrating Oil Product Data Sheet

General Information

- Penetrating oil & heavy-duty spray lubricant
- Protects from rust & corrosion, even in highly corrosive & extreme humidity environments
- Better alternative to an aerosol can - spray bottle is safer & full of product - no money wasted on hazardous ozone-depleting substances
- Contains Muscle MT-10™ Metal Treatment technology & PL-10™ Power-Lift Grease for enhanced lubrication

Typical Applications

- Rusty nuts & bolts
- Heavy-duty industrial chains
- Braided steel cables
- Wire rope
- Chain drives
- Drag lines
- Linkages
- Open roller bearings & sleeve bearings
- Couplings
- Bushings
- Pulleys
- Hinges
- Augers
- Tools
- Metal mechanisms
- Assembly lube during transmission rebuilds
- Protection during long-term storage
- Any other industrial, automotive, or commercial area of lubrication that requires an external, heavy-duty spray lubricant or penetrating oil.

Key Features & Benefits

- Fast-acting penetrating oil
- Heavy-duty lubricating action
- Penetrates into hard-to-reach areas
- Loosens seized & corroded nuts & bolts or other frozen metal mechanisms
- Protects against rust & corrosion - even in extreme humidity & salt water environments

Availability

- 16-oz. bottle with trigger sprayer (474 ml)
- 1 & 5 U.S. gallon containers (3.8 & 18.9 L)
- 55 U.S. gallon drum (208 L)

Directions for Use

Wipe off exposed metal surfaces. Spray SL-10™ directly on areas to be lubricated. After applying SL-10™, wipe away excess if necessary with a dry cloth. Repeat in especially stubborn applications.

Typical Properties

| | |
|--|----------------------------------|
| Boiling Point | 399°F (204°C) |
| Flash Point | 295°F (146°C) D93 |
| Specific Gravity @ 60°F, g/cm ³ | 0.933 |
| Density | ~ 7.786 lbs per gal (US) |
| Viscosity @ 100°C, cSt | ~ 5.1 |
| Freezing Point | ~ - 30 to - 36°F (- 34 to -38°C) |
| Pour Point | - 33°F (- 36°C) |
| Rust Test (1 pass/0 fail) | 1.0 |
| Odor | Mild petroleum |
| Color & Appearance | Milky amber low viscosity liquid |
| Solubility in Water | Insoluble |

Copyright 1986-2012 Muscle Products Corp.
Rev. 9/2012

